

LTS2070 Skin Temperature Sensor

Lt Sensors Series

Description

The Lt Sensors Skin Temperature Probe contains a small biomedical ship thermistor in a metal case with strain relief between the cable and thermistor. The thermistor is designed to operate from 0 °C to 50 °C.



Operation

The thermistor is a small, ceramic-encapsulated metal-oxide semiconductor. It exhibits a characteristic non-linear inverse relationship between resistance and temperature (see graph below) that allows it to be used as a temperature sensor. The relatively large change in resistance as a function of temperature ($\sim 4\%/^{\circ}\text{C}$) gives a signal response far greater than thermocouples and resistance temperature devices (RTD). The metal case of the probe is held flat against the skin of the subject and is usually taped into position. It can be cold-sterilized between subjects.

To use the Skin Temperature Sensor, plug the sensor into the USB port of a laptop or desktop computer, with a Windows operating system. Alternatively, plug the sensor into a USB hub connected to that computer. A green LED on the connector housing indicates the transducer is receiving power and is ready for use.

Application

The Lt Sensor Skin Temperature Sensor is specifically designed for continuous biomedical temperature monitoring requiring repeatability, high sensitivity, and rapid response.

Typical Data



Recording of skin surface temperature following wind exposure

Caution

Read "Statement of Intended Use" on our website.

Specifications

Thermal response time:	still air 45 s
Operating range:	0°C to 50°C
Accuracy:	±0.25°C
Height x Diameter:	4.5 x 12 mm (0.18" x 0.47")
Cable length:	2.0 m (6.5')
Connector:	USB
Cup/barrel:	stainless steel filled with epoxy resin

All specifications were tested at the time of printing and are subject to change.

Ordering Information

LTS2070 Skin Temperature Sensor

For use with:
Laptop or desktop computer with Windows operating system